


Thyristor Surge Suppressors



Features

- Low switching voltage
- Low on-state voltage
- Does not degrade surge capability after multiple surge events within limit
- Fails short circuit when surged in excess of ratings
- Low Capacitance

Typical Applications

- Protect circuit

Mechanical Data

- **Package:** DO-214AC (SMA)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102



■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Max
Storage temperature	T _{stg}	°C	-55~+150
Junction temperature	T _j	°C	-55~+150

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

Part Number	V _{drm} @I _{drm} =5μA (V)	V _s @100V/μs (V)	V _t @I _t =2.2Amps (V)	I _{drm} @V _{drm} (μA)	I _s (mA)	I _t (A)	I _h (mA)	Co @1MHz,2V bias (pF)
	Min	Max	Max	Max	Max	Max	Min	Typ.
P0080T_	6	25	4	5	800	2.2	30	60
P0300T_	25	40	4	5	800	2.2	50	55
P0640T_	58	77	4	5	800	2.2	120	55
P0720T_	65	88	4	5	800	2.2	120	55
P0900T_	75	98	4	5	800	2.2	120	55
P1100T_	90	130	4	5	800	2.2	120	55
P1300T_	120	160	4	5	800	2.2	120	55
P1500T_	140	180	4	5	800	2.2	120	55
P1800T_	170	220	4	5	800	2.2	120	55
P2300T_	190	260	4	5	800	2.2	120	55
P2600T_	220	300	4	5	800	2.2	120	55
P3100T_	275	350	4	5	800	2.2	120	55
P3500T_	320	400	4	5	800	2.2	120	55
P4000T_	360	460	4	5	800	2.2	120	55



SMAJ TSS SERIES

For individual “TA” and “TB” surge ratings, see table below.

Series	Ipp 10/700us (A)	Ipp 8/20us (A)	Ipp 10/1000us (A)
	Min	Min	Min
A	50	150	45
B	100	250	80

■ Characteristics (Typical)

FIG1: V-I Characteristics




FIG2: tr*td Pulse Wave-form




FIG3: Normalized Vs Change versus Junction Temperature





FIG4: Normalized DC Holding Current




■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
P0080TA-P4000TB	F1	Approximate 0.059	5000	10000	80000	13" reel




SMAJ TSS SERIES

■ Outline Dimensions



DO-214AC(SMA)		
Dim	Min	Max
A	1.25	1.58
B	2.40	2.83
C	4.00	4.75
D	1.90	2.30
E	4.93	5.28
F	0.76	1.41
G	0.08	0.20
H	0.15	0.31

■ Suggested Pad Layout



DO-214AC(SMA)	
Dim	Millimeters
P1	4.00
P2	1.50
P3	6.50
Q1	2.50
Q2	1.70



SMAJ TSS SERIES

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.