


High Speed Switching Diodes



Features

- Moisture sensitivity level 1
- Reverse voltage: 300V
- Average forward current : 225mA

Application

- High frequency rectifier
- Signal switching

Mechanical data

- **Package:** SOD-123
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Value
Device marking code			4P
Repetitive peak reverse voltage	V _{RRM}	V	300
Average Forward current	I _{FAV}	mA	225
Repetitive peak forward current	I _{FRM}	mA	625
Non-repetitive surge peak forward current @ t=1s half-sine wave	I _{FSM}	A	1
Non-repetitive surge peak forward current @ t=1us square wave			4
Power dissipation	P _D	mW	400
Junction temperature	T _J	°C	-55 to +150
Storage temperature	T _{STG}	°C	-55 to +150



BAV3004W

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Typ	Max
Breakdown voltage	V _R	V	I _R =150uA	300		
Forward voltage	V _{F1}	V	I _F =20mA		0.78	0.87
	V _{F2}	V	I _F =100mA		0.93	1
	V _{F3}	V	I _F =200mA		1.03	1.25
Reverse leakage current	I _{R1}	nA	V _R =240V		30	100
	I _{R2}	uA	V _R =240V, T _J =150°C		35	100
Junction capacitance	C _j	pF	V _R =0V, f =1MHZ		1	5
Reverse recovery time	T _{rr}	ns	I _F = I _R =30mA, I _{rr} =3mA, R _L =100Ω			50

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	312.5
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	250

Note:

(1) Thermal resistance from junction to ambient and from junction to case mounted on P.C.B. with 8mm*9mm copper pad areas



■ Characteristics

Fig 1: P_D -Ta Curve




Fig 2: Capacitance Capability




Fig 3: Typical Forward Characteristics





Fig 4: Typical Reverse Characteristics






BAV3004W

■ Ordering Information

Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
BAV3004W	F2	Approximate 0.011	3000	30000	120000	7" reel
BAV3004W	F3	Approximate 0.011	10000	/	210000	13" reel


■ Outline Dimensions



TOP VIEW




SIDE VIEW



SIDE VIEW

DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MM	MAX
A	0.140	0.152	3.550	3.850
B	0.100	0.112	2.550	2.850
C	0.055	0.071	1.400	1.800
D	0.037	0.053	0.950	1.350
E	0.020	0.028	0.510	0.710
G	0.006	0.018	0.150	0.450
H	0.003	0.010	0.080	0.250
J	0.000	0.006	0.000	0.150
θ	0	8°	0	8°

■ Suggested Pad Layout



UNIT: mm



BAV3004W

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.